



# PRODUCT SPECIFICATION

## THREADED METAL CURVE

| TYPE          | COMPOSITION    | Ø OUT mm    | TOLERANCE mm | Ø INS. mm | LENGTH mm | TOL. ER. mm | INS. RADIUS (+-2) | ANG.º | + - ANGº | THREAD LENGTH +-1 | CURVES/BOX |
|---------------|----------------|-------------|--------------|-----------|-----------|-------------|-------------------|-------|----------|-------------------|------------|
| AISCAN-CMR-16 | STEEL          | 16          | +0 -0,3      | 13,6      | 165       | +5          | 105               | 90    | 3        | 15                | 10         |
| AISCAN-CMR-20 | “              | 20          | +0 -0,3      | 17,6      | 175       | +5          | 110               | 90    | 3        | 15                | 10         |
| AISCAN-CMR-25 | “              | 25          | +0 -0,3      | 22,6      | 185       | +5          | 130               | 90    | 3        | 17                | 10         |
| AISCAN-CMR-32 | “              | 32          | +0 -0,3      | 29,2      | 215       | +5          | 145               | 90    | 3        | 20                | 10         |
| AISCAN-CMR-40 | “              | 40          | +0 -0,4      | 37,2      | 265       | +5          | 165               | 90    | 3        | 22                | 5          |
| AISCAN-CMR-50 | “              | 50          | +0 -0,4      | 47,2      | 325       | +5          | 185               | 90    | 3        | 27                | 5          |
| AISCAN-CMR-63 | “              | 63          | +0 -0,5      | 59,6      | 510       | +5          | 330               | 90    | 3        | 30                | 3          |
| EDITION DATE  | EDITION NUMBER | CARD NUMBER |              |           |           |             |                   |       |          |                   |            |
| 2009/02       | 2              | FT-CMR      |              |           |           |             |                   |       |          |                   |            |

| CHARACTERISTICS ACCORDING TO STANDARD<br>UNE-EN 61386-21 |                 | CHARACTERISTICS LABEL<br><i>Each label indicates:</i>             | USE                                   |
|--|-----------------|---|---------------------------------------|
| CODE:  | 555711542010    | Each curve specifies the type, nominal, CE marking, date and hour | <b>IN THE TUBE TYPE: "AISCAN-TMR"</b> |
| CRUSHING STRENGTH:                                       | >4000 N         |   |                                       |
| IMPACT RESISTANCE:                                       | >20,4J at -45°C |   |                                       |
| OPERATING TEMPERATURE RANGE:                             | -45+400°C       |   |                                       |
| RIGID:   | YES             |   |                                       |
| CORROSION RESISTANCE:                                    | MEDIUM          |   |                                       |
| FLAME PROPAGATE:   | NO              |   |                                       |
| COLOUR:  | ZINC            |   |                                       |
| NOT CORROSIVE INTERIOR PAINT                             |                 |   |                                       |

**- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WITHOUT PREVIOUS ADVERTISEMENT.-**