



# PRODUCT SPECIFICATION

## AISCAN TME

TYPE	COMPOSITION	Ø OUT. mm	TOLERANCE mm	Ø INS. ± TOL. mm	LENGTH mm	TOLER. mm	TUBES MALLET	LABELS
AISCAN-TME-16	STEEL	16	+0 -0,3	14 +0 -0,3	3000	+10 -5	19	1
AISCAN-TME-20	"	20	+0 -0,3	18 +0 -0,3	3000	+10 -5	10	1
AISCAN-TME-25	"	25	+0 -0,4	23 +0 -0,4	3000	+10 -5	10	1
AISCAN-TME-32	"	32	+0 -0,4	29,6 +0 -0,4	3000	+10 -5	7	1
AISCAN-TME-40	"	40	+0 -0,4	37,6 +0 -0,4	3000	+10 -5	5	1
AISCAN-TME-50	"	50	+0 -0,5	47,2 +0 -0,5	3000	+10 -5	5	1
AISCAN-TME-63	"	63	+0 -0,6	60 +0 -0,6	3000	+10 -5	3	1



EDITION DATE	EDITION NUMBER	CARD NUMBER
2012/03	4	EP-TME

### CHARACTERISTICS ACCORDING TO STANDARD UNE-EN 61386-21

CODE:	555711542010
CRUSHING STRENGTH:	>4000 N
IMPACT RESISTANCE:	>20,4J a -45°C
OPERATING TEMPERATURA RANGE:	-45 +400°C
RIGID:	YES
EXTERNAL INFLUENCES:	IP 54
FLAME PROPAGATE:	NO
COLOUR:	ZINC
NON CORROSIVE INTERIOR PAINT	

### CHARACTERISTICS LABEL

*Each label indicates:*

Type, nominal, number of meters, standard UNE-EN applied, "CE" marked,  
Storage and use instructions, Bar code EAN-13, date, control number and manufacture line.

EACH TUBE BAR INDICATES: type, nominal, standard UNE-EN applied, code, date, hour, manufacture line and "CE" marked.

### ACCESSORY TUBE

**MTME**

**- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT.**