



PRODUCT SPECIFICATION

AISCAN TMEG

TYPE	COMPOSITION	Ø OUT. mm.	TOLERANCE mm.	Ø INS. ±TOL. mm.	LENGTH mm.	TOLER. mm.	WALL THICKNESS	TUBES MALLET	LABELS
AISCAN-TMEG-16	STEEL	16	+0 -0,3	14 +0 -0,3	3000	+10 -5	1	19	1
AISCAN-TMEG-20	"	20	+0 -0,3	18 +0 -0,3	3000	+10 -5	1	10	1
AISCAN-TMEG-25	"	25	+0 -0,4	23 +0 -0,4	3000	+10 -5	1	10	1
AISCAN-TMEG-32	"	32	+0 -0,4	29,6 +0 -0,4	3000	+10 -5	1,2	7	1
AISCAN-TMEG-40	"	40	+0 -0,4	37,6 +0 -0,4	3000	+10 -5	1,2	5	1
AISCAN-TMEG-50	"	50	+0 -0,5	47,2 +0 -0,5	3000	+10 -5	1,5	5	1
AISCAN-TMEG-63	"	63	+0 -0,6	60 +0 -0,6	3000	+10 -5	1,5	3	1
EDITION DATE	EDITION NUMBER	CARD NUMBER							
2018/12	6	EP-TMEG							

CHARACTERISTICS ACCORDING TO STANDARD UNE-EN 61386-21	
CODE:	555711544010
CRUSHING STRENGTH:	>4000 N
IMPACT RESISTANCE:	>20,4J a -45°C
OPERATING TEMPERATURA RANGE:	-45 +400°C
RIGID:	YES
EXTERNAL INFLUENCES:	IP 54
FLAME PROPAGATE:	NO
COLOUR:	ZINC
NON CORROSIVE INTERIOR PAINT	
COATING THICKNESS:	45 µm
COATING:	HOT DIP GALVANISED IN ACCORDING TO UNE-EN ISO 1461:2010

CHARACTERISTICS LABEL <i>Each label indicates:</i>
Type, nominal, number of meters, standard UNE-EN applied, "CE" marked, Storage and use instructions, Bar code EAN-13, date, control number and manufacture line.
EACH TUBE BAR INDICATES: type, nominal, standard UNE-EN applied, code, date, hour, manufacture line and "CE" marked.

ACCESSORY TUBE
MTMEG

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT.