

## **PRODUCT SPECIFICATION**

## **OMEGA BRACKET MULTIFUNCTION (SENDZIMIR)**

				ALLOWABLE	
ТҮРЕ	MATERIAL	COATING	A	WORKING LOAD (N/m)	PACKING (Units)
AISCAN-SOMS 10	METALLIC	SENDZIMIR GALVANISED	100	1550	5
AISCAN-SOMS15	w	W	150	1302	5
AISCAN-SOMS20	w	W	200	1010	5
AISCAN-SOMS30	"	W	300	638	5
AISCAN-SOMS40	w	W	400	470	5
EDITION DATE	EDITION NUMBER	DOCUMENT ID.			
2016/01	1	EP - SOMS			

CHARACTER			
DESCRIPTION:	SENDZIMIR GALVANISED OMEGA BRACKET MULTIFUNCTION	OBSERVATIONS	
COATING:	SENDZIMIR GALVANISED IN ACCORDING TO UNE-EN ISO 10346:2010		
MATERIAL:	METALLIC	THE INSTALLATION OF THIS PRODUCT WILL BE CARRIED OUT ACCORDING TO THE R.E.B.T.	
ELECTRICAL CONTINUITY:	YES		
FLAME PROPAGATE:	NO		
OPERATING TEMPERATURE RANGE:	-40 °C / 150 °C		
RESISTANCE TO CORROSION:	TYPE 3		
IMPACT RESISTANCE:	20 J TO -40 °C		