



PRODUCT SPECIFICATION

PRESSURE CUFF EHF

TYPE	COMPOSITION	Ø OUT mm	Ø INS. MAX.	Ø INS. MIN.	TOLER. mm	TOP DIAMETER INS.	LENGHT	TOLER. LENGHT	COLOUR
AISCAN-MEHF-16	HALOGEN-FREE RIGID TERMOPLASTIC	19,3	16,1	15,5	+0,2	14	50	+1	GREY
AISCAN-MEHF-20	“	24,7	20,2	19,5	+0,2	18	55	+1	“
AISCAN-MEHF-25	“	29,8	25,2	24,5	+0,2	23	64	+1	“
AISCAN-MEHF-32	“	36,5	32,2	31,5	+0,2	30	74	+1	“
AISCAN-MEHF-40	“	44,2	40,2	39,5	+0,2	38	80	+1	“
AISCAN-MEHF-50	“	54,3	50,2	49,5	+0,2	48	98	+1	“
AISCAN-MEHF-63	“	67,2	63,4	62,4	+0,2	62	118	+1	“
EDITION DATE	EDITION NUMBER	CARD NUMBER							
2007/12	2	EP-MEHF							

ACCORDING TO STANDARD UNE-EN 50267-2-2 [old UNE-21-147(2)/IEC-754(2)] about "Determination of the degree of acidity of gases for materials by measuring pH and conductivity".
ACCORDING TO STANDARD UNE-EN 21031-15:2008 "Determination of halogens. Elementary test".

- **THESE ACCESSORIES ARE USED FOR THE TUBES "AISCAN-EHF" IN ACCORDING TO UNE-EN 60423**

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISEMENT-