



PRODUCT SPECIFICATION

AISCAN EHF

TYPE	COMPOSITION	Ø OUT mm	TOLERANCE mm	Ø INS. mm	LENGTH m	TOLER. mm	SLEEVES	LABELS	TUBES MALLET	Nº TIES
AISCAN-EHF-16	HALOGEN FREE TERMOPLASTIC	16	+0 -0,3	11,8	3000	+10 -5	1	1	19	3
AISCAN-EHF-20	“	20	+0 -0,3	15,7	3000	+10 -5	1	1	19	3
AISCAN-EHF-25	“	25	+0 -0,4	20,1	3000	+10 -5	1	1	19	3
AISCAN-EHF-32	“	32	+0 -0,4	26,5	3000	+10 -5	1	1	10	3
AISCAN-EHF-40	“	40	+0 -0,4	34,5	3000	+10 -5	1	1	10	3
AISCAN-EHF-50	“	50	+0 -0,5	42,9	3000	+10 -5	1	1	5	3
AISCAN-EHF-63	“	63	+0 -0,6	56,2	3000	+10 -5	1	1	5	3
EDITION DATE	EDITION NUMBER	CARD NUMBER								
2014/05	4	EP-EHF								

CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-21	
CODE:	442112540010
CRUSHING STRENG:	>1250 N
IMPACT RESISTANCE:	>6J at -5°C
OPERATING TEMPERATURE RANGE:	-5+60°C
RIGID	YES
DIELECTRICAL RIGIDITY:	>2000 V
ISOLATION RESISTANCE:	>100 MOhm
EXTERNAL INFLUENCES:	IP54
FLAME PROPAGATE:	NO
COLOUR:	GREY RAL. 7035

CHARACTERISTICS LABEL
<i>Each label indicates:</i>
Type, nominal, number of meter, standard UNE-EN applied, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.
EACH TUBE BAR INDICATES: type, nominal, standard UNE-EN applied, code, date, hour, manufacture line and "CE" marked.

ACCESORY TUBE
TYPE "AISCAN-HF" WICH PLUGS IN. HALOGEN FREE

ACCORDING TO STANDARD UNE-EN 50267-2-2 [old UNE-21-147(2)/IEC-754(2)] about "Determination of the degree of acidity of gases for materials by measuring pH and conductivity".
 ACCORDING TO STANDARD UNE-EN 21031-15:2008 "Determination of halogens. Elementary test".

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT-