



PRODUCT SPECIFICATION

AISCAN BMPI - 60

TYPE	MATERIAL	COATING	A	B	ALLOWABLE WORKING LOAD (N/m)	PACKING (meters)	PLAIN	
AISCAN-BMPI-606	STAINLESS STEEL	-	60	60	338	24		
AISCAN-BMPI-610	"	-	100	60	411	12		
AISCAN-BMPI-615	"	"	150	60	338	12		
AISCAN-BMPI-620	"	"	200	60	423	12		
AISCAN-BMPI-630	"	"	300	60	358	6		
AISCAN-BMPI-640	"	"	400	60	388	6		
AISCAN-BMPI-650	"	"	500	60	351	6		
AISCAN-BMPI-660	"	"	600	60	315	6		
EDITION DATE	EDITION NUMBER	CARD NUMBER						
2013/10	2	EP-BMPI 60						

CHARACTERISTICS ACCORDING TO STANDARD IEC 61537:2006	
DESCRIPTION:	MESH CABLE TRAY STAINLESS STEEL.
COATING:	STAINLESS STEEL, AISI 304
MATERIAL:	METALLIC
ELECTRICAL CONTINUITY:	YES
FLAME PROPAGATE:	NO
OPERATING TEMPERATURE RANGE:	-40 °C / 150 °C
RESISTANCE TO CORROSION:	TYPE 9A
IMPACT RESISTANCE:	20 J TO -40 °C
ALLOWABLE WORKING LOAD (CTA):	DISTANCE BETWEEN SUPPORTS (1,5 METERS)

OBSERVATIONS
FOR THE UNION BETWEEN BRACKETS WILL BE REQUIRED THE USE OF 2 TO 4 SETS OF UNION (CUBS), DEPENDING THE WIDTH OF THE TRAY.
WITH ALL EDGES ROUNDED.
ACCESORIES
TRAY ATTACHMENT ASSEMBLY (CUB) UNIVERSAL MESH CABLE TRAY COVER (TUBC) OMEGA BRACKET (SO)

THE INSTALLATION OF THIS PRODUCT WILL BE CARRIED OUT ACCORDING TO THE R.E.B.T.