



# PRODUCT SPECIFICATION

## PLUG METALIC CURVE

TYPE	COMPOSITION	Ø OUT mm	TOLERA NCE mm	Ø INS. mm	LENGTH mm	TOLER. mm	RADIUS	ANG.º	+ - ANGº	CURVES / BOX
AISCAN-CME-16	STEEL	16	+0 -0,3	13,6	165	+10 -5	105	90	3	10
AISCAN-CME-20	“	20	+0 -0,3	17,6	175	+10 -5	110	90	3	10
AISCAN-CME-25	“	25	+0 -0,3	22,6	185	+10 -5	130	90	3	10
AISCAN-CME-32	“	32	+0 -0,3	29,2	215	+10 -5	145	90	3	10
AISCAN-CME-40	“	40	+0 -0,4	37,2	265	+10 -5	165	90	3	5
AISCAN-CME-50	“	50	+0 -0,4	47,2	325	+10 -5	185	90	3	5
AISCAN-CME-63	“	63	+0 -0,5	59,6	510	+10 -5	330	90	3	3
EDITION DATE	EDITION NUMBER	CARD NUMBER								
2009/02	2	EP-CME								

CHARACTERISTICS ACCORDING TO STANDARD UNE-EN 61386-21	CHARACTERISTICS LABEL <i>Each label indicates:</i>	USE
CODE: 555711542010	Each curve specifies the type, nominal, CE marking, date and hour	<b>IN THE TUBE TYPE: "AISCAN-TME"</b>
CRUSHING STRENG: >4000 N		
IMPACT RESISTANCE: >20J at -45°C		
OPERATING TEMPERATURE RANGE: -45+400°C		
RIGID: YES		
CORROSION RESISTANCE: MEDIUM		
FLAME PROPAGATE: NO		
COLOUR: ZINC		
NOT CORROSIVE INTERIOR PAINT		

**- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT.-**